

Rustler Harrow

Specifications and Options

| Models | 5-55 | 5-68 | 5-78 | 5-90 | 7-58 | 7-72 | 7-82 |
|--|---|---------------------------|---------------------------|---------------------------|---|---------------------------|--------------------------|
| Working Width | 55 feet (16.76 m) | 68 feet (20.72 m) | 78 feet (23.77 m) | 90 feet (27.43 m) | 58 feet (17.68 m) | 72 feet (21.95 m) | 82 feet (25 m) |
| Weight | 11,950 lb 5,420 kg | 13,560 lbs. (6,151 kg) | 14,720 lbs. (6,677 kg) | 16,500 lbs. (7,484 kg) | 13,500 lbs (6,123 kg)) | 15,500 lbs (7,030 kg) | 19,900 lbs (9,026 kg) |
| Transport | | | | | | | |
| - Width | 14' 9" (4.5m) | 14' 9" (4.5m) | 14' 9" (4.5m) | 16' 3" (4.9m) | 14' 9"(4.5m) | 14' 9" (4.5m) | 16'6"(5.03m) |
| - Height | 11' 8" (3.6m) | 11' 8" (3.6m) | 11' 8" (3.6m) | 11' (3.1m) | 12'7"(3.84m) | 12'7"(3.84m) | 12'7"(3.84m) |
| - Length | 44' 8"(13.7m) | 51'10"(15.8m) | 55'10"(17.0m) | 64'10"(20m) | 38'1"(11.6m) | 52'8"(16.0m) | 60'10"(18.54m) |
| Tires | | | | | | | |
| - Main Frame | (2) 16.5L x 16.1 | | | (2)21.5Lx16.1 | (2) 16.5L x 16.1 | | (2) 21.5Lx16.1 |
| - Wing Frame (1 per wing) | (2) 12.5L x 15 | | | (2)16.5Lx16.1 | (2) 12.5L x 15 | | (2) 16.5Lx16.1 |
| Harrow Sections | | | | | | | |
| - Tine | Standard - 9/16" diameter x 28" length Optional - 5/8" diameter x 28" length | | | | 1/2" diameter x 24' length | | |
| - Tine Tips | Max Life carbide wear coating - bottom 4" (102 mm) | | | | Max Life carbide wear coating - bottom 4" (102 mm) | | |
| - Tine Spacing | 2.6" (66 mm) | | | | 1.4" (35 mm) | | |
| - Tine Adjustment | Hydraulic | | | | Hydraulic | | |
| - Tine Angle | 40 - 85 Degrees | | | | 40 - 85 Degrees | | |
| - Frame System | Parallel Linkage with 12" of travel | | | | Parallel Linkage with 12" of travel | | |
| - Bars Per Section | 5 | | | | 7 | | |
| - Bars Spacing | 18" (457 mm) | | | | 14" (355 mm) | | |
| - Section Width | 5 - 11' | 2 - 6.5' and 5 - 11' | 7 - 11' | 2 - 6.5' and 7 - 11' | 5 - 11.5' | 2 - 6.5' and 5 - 11.5' | 7 - 11.5' |
| Auto-Fold with hydraulic pivoting end wheels | Standard | | | | Standard | | |
| Auto-Lock Draft Arms | Standard | | | | Standard | | |
| Cart Frame | 4" x 8" tubular steel with 1/4" wall (203mm x 100mm x 6.4mm) | | | | 4" x 8" tubular steel with 1/4" wall (203mm x 100mm x 6.4mm) | | |
| Harrow Frame | 8" x 8" tubular steel with 3/8" wall (203mm x 203mm x 9.5mm) | | | | 8" x 8" tubular steel with 3/8" wall (203mm x 203mm x 9.5mm) | | |
| Hydraulics | 3 hydraulic remotes required | | | | 3 hydraulic remotes required | | |
| Safety Lights | Standard | | | | Standard | | |
| Safety Chain | Standard | | | | Standard | | |

Specifications are estimates and subject to change.

MORRIS

CORPORATE OFFICE

#205 - 2100 Airport Drive Saskatoon, SK Canada S7L 6M6

p. 306.933.8585 f. 306.933.8626

Questions? email: info@morrisequipment.ca