

CX 8105

SEEDING SYSTEM

Base Size		25' (7.62 m)	31' (9.45 m)
Total Weight	- 10" (25.4 cm) spacing	20,119 lbs. (9145 kg)	21,404 lbs. (9729 kg)
	- 12" (30.5 cm) spacing	19,316 lbs. (8780 kg)	20,535 lbs. (9334 kg)
Axle Weight (Empty)	- 10" (25.4 cm) spacing	12,583 lbs. (5720 kg)	13,355 lbs. (6071 kg)
	- 12" (30.5 cm) spacing	12,100 lbs. (5500 kg)	12,833 lbs. (5834 kg)
Hitch Weight (Empty)		1672 lbs. (760 kg)	1672 lbs. (760 kg)
Working Width	- 10" (25.4 cm)	25' (7.62 m)	30' (9.14 m)
	- 12" (30.5 cm)	25' (7.62 m)	31' (9.45 m)
Number of Shanks	- 10" (25.4 cm)	30	36
	- 12" (30.5 cm)	25	31
Frame Width	- Main	5' (1.524 m)	5' (1.524 m)
	- Wing Inner	10' (3.048 m)	13' (3.962 m)
Transport Position	- Width	9' 10" (3 m)	9' 10" (3 m)
	- Height	13' 9" (4.19 m)	16' 2" (4.93 m)
	- Length	36' 2" (11 m)	36' 2" (11 m)
Tires	- Cart	(2) 600/50-22.5 Alliance Tire	(2) 600/50-22.5 Alliance Tire
	- Main Frame Rear Wheels	(4) 12.5L x 15 FI Load Range F	(4) 12.5 L x 15 FI Load Range F
	- Wing Frame Front Castor Wheels (1 per wing)	(2) 12.5SL x 15 12 Ply Rating	(2) 12.5SL x 15 12 Ply Rating
	- Wing Frame Rear Wheels (1 per wing)	(2) 12.5SL x 15 12 Ply Rating	(2) 12.5SL x 15 12 Ply Rating
Tank Capacity	- Front Tank	60 Bu (2110 L)	
	- Rear Tank	45 Bu (1585 L)	
	- Third Tank - Optional	10 Bu (350 L)	
	- Total	2 Tanks - 105 Bu (3695 L) With third Tank - 115 Bu (4045 L)	
Tank Screens		Standard	
Fan	- Rated Speed	Up to 5,000 r.p.m.	
	- Impeller Diameter	13" (33 cm) Diameter	
	- Noise Level	97.3 dB	
Hydraulic Drive - Blower drive piston type orbit motor 12 cc (Closed Centre or Closed Centre load Sensing systems required)		Blower and VRT (Minimum 21 U.S. gal./min.) (Minimum 80 L/min.) (Minimum 2100 p.s.i.) (Minimum 14469 kPa)	
Metering	- Variable Rate (VRT)	Standard	
	- GPS Compatible VRT	Optional	
Opener	- Trip Out Force	Increases proportionally with Packing Force to a max. of 600 lbs. (272 kg)	
	- Packing Force	Adjustable from 70 lbs. to 170 lbs. (31.7 kg to 77.1 kg)	
	- Packer Wheel	4.50" x 16" Semi Pneumatic Otico tire 4.80" x 16" Semi Pneumatic or Pneumatic 5.50" x 16" Semi Pneumatic Otico tire 5.50" x 16" Semi Pneumatic 4.00" x 16" "V" Crown	
Opener to Ground Clearance		12" (30.5 cm)	
Frame to Ground Clearance		32" (81 cm)	
Frame Depth		94" (238.8 cm) center to center	
Rank to Rank Spacing		47" (119.4 cm) center to center	
Number of Ranks		3 Rows	
Shank to Shank Spacing		30" (76.2 cm) on 10" (25.4 cm) spacing 36" (91.4 cm) on 12" (30.5 cm) spacing	
Weight Kit		Optional	
Safety Lights		Standard	
Safety Chain		Standard	

Specifications are estimates and subject to change.



MORRIS