

FIELD PRO

HEAVY HARROW

Base Size	50 feet (15.24 m)	70 feet (21.33 m)
5-Bar Harrows - 10' (3.05 m) Wide x 72" (183 cm) Deep	Standard	Standard
Tines - Straight 9/16" (1.43 cm) Diameter x 27 1/4" (69 cm) Long	Standard	Standard
Hydraulic Tine Adjustmтт	Optional	Optional
Main Frame -Single Axle -Tire Size -	(2) 16.5L x 16.1 6 ply rating	(2) 16.5L x 16.1 6 ply rating
Wing Axle (1 per wing) - Tire Size	(2) 9.5L x 15 6 ply rating	(2) 9.5L x 15 6 ply rating
Wing Transport Axle - (1 per wing) - Tire Size	(2) ST225/75R15 SL Load Range D	(2) 11L x 15 FI Load Range D
Lift Cylinders *	(2) 3 1/2" (9 cm) Dia. x 24" (61 cm)	(2) 4" (10 cm) Dia. x 24" (61 cm)
Cart Frames - 2" (5 cm) x 8" (20.3 cm) Structural Tubing	Standard	Standard
Main Frame - 6" (15 cm) x 8" (20.3 cm) Structural Tubing	Standard	Standard
Wing Frame - 6" (15 cm) x 8" (20.3 cm) Structural Tubing	Standard	Standard
Harrow Arms - 1 1/2" (3.81 cm) x 3" (7.62 cm) Structural Tubing	Standard	Standard
Safety Chain	Standard	Standard
Safety Lights	Standard	Standard
Weight	9,310 lbs. (4,232 kg)	13,800 lbs. (6,273 kg)
Harrow Tine Length	27 1/4" (69 cm)	
Harrow Tine Diameter	9/16" (1.43 cm)	
Harrow Tine Spacing	2 inches (5 cm)	
Harrow Tine Angle Degree Range	30 - 90	
Overall Working Length	27' 10" (5.43 m)	
Frame Ground Clearance	20" (51 cm)	
Transport Height	11' 9" (3.58 m)	
Transport Length	40' (12.2 m)	50' (15.2 m)
Transport Width	14' 7" (4.45 m) at a Height of 9' (2.74 m)	

*NOTE: Minimum Hydraulic Pressure 1,950 P.S.I. (13,435 kPa)



MORRIS